

Multi-button

# SIP Video Door Phone


**C88**

HD Audio  
 720p HD Camera  
 2.3" Graphic LCD Display  
 Unlock door with DTMF,  
 local password or IC/ID card  
 reader



720P



HD



PoE



## Overview

The C88 is a Multi-button SIP Door Phone with the integrated HD camera and advanced audio system with the echo cancellation function. It supports H.264 video compression format and delivers excellent video quality in 720p video resolutions. with the C72 touch screen control pad, you can speak to visitors and view video from camera at any time.

The C88 offers keyless control and convenience for the users which supports many ways of opening the door without a key. The door can be open remotely but also local password or IC/ID card if there is an electronic door lock. It's ideal for control communication and security over internet such as business, institutional and residential applications .

## Video Features

- 2M Pixels color CMOS camera
- Maximum image transfer rate: 720p -30fps
- Video Codec: H.264
- Resolution: up to 1280 x 720
- Viewing Angle: 80° (H), 60° (V)
- Minimum Illumination: 0.1lux

## Access Control

- One SIP line, Dual SIP servers
- Door Access: DTMF tones, password, IC/ID card
- Door Phone features:
- Full-duplex
- Default auto answer
- Action URL/Active URI remote control
- Speed Dial

## Administration Features

- Auto provisioning:  
FTP/TFTP/HTTP/HTTPS/PnP
- HTTP/HTTPS Web Management
- Configuration keypad-based management
- SNMP/TR069
- NTP/Daylight Saving Time
- Firmware Upgrade via Web
- Syslog
- Configuration backup/restore

## Environments

- Operating Temperature: -20~60 °C
- Storage Temperature: -40~70 °C
- Relative Humidity: 10~90%

## Audio Features

- HD voice
- Two-way audio stream
- Wideband codec: G.722
- Narrowband codec: PCMA, PCMU, G.729, G723\_53, G723\_63, G726\_32
- Echo cancellation with G.168
- Voice activity detection (VAD)
- Comfort noise generator(CNG)
- Built-in Micro and speaker
- Acoustic echo cancellation audio output

## Protocols & Network

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP over TLS, SRTP
- RTSP
- TCP/IPv4/UDP
- RTP/RTCP, RFC2198, 1889
- HTTP/HTTPS/FTP/TFTP
- ARP/RARP/ICMP/NTP
- DNS SRV/ A Query/NATPR Query
- Primary /Secondary DNS
- STUN, Session timer
- 802.1p/q, DSCP
- DHCP/Static/PPPoE
- DTMF Mode: In-Band, RFC2833 and SIP INFO

## Physical Specifications

- Display: 2.3" 132x64 graphic LCD with Backlight
- Numeric keypad
- Card reader area
- Aluminum surface, Metal bottom shell
- Power Supply: DC 12V1A or 802.3af PoE
- Power Requirements: 802.3af PoE class 3
- IEEE 802.3af Power-over-Ethernet
- 1xRJ45 10/100M Ethernet jacks
- Wall-mounted installation
- Dimensions: 260\*130\*32 mm

## Technical Support

Visit Dinstar web site (<http://www.dinstar.com/>) for more product documents, FAQ, and more.  
For better service, please contact with [support@dinstar.com](mailto:support@dinstar.com) or online support.